



PCB Layout Diagram
Top View

NOTE:

1. MATERIAL:

- a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
- b. CONTACT: PHOSPHOR BRONZE (SURFACE PLATING: Sn100u")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C

TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.20MM	Sn-Plating
TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.20MM	Sn-Plating
HOUSING	1	PBT	BLACK
PART NAME	QTY	MATERIAL	PLATING & COLOR
A		NEW	
ECN NO.	REV.	DATE.	DESCRIPTION.

APPROVALS		DATE	TITLE: 電池座 反向	
DRAWN	ZHWEI.CHEN	2015.07.07		
CHECKED			PART NO.	GP07-CR1220-03
APPROVALS			UNIT: mm	SCALE: 1:1
TOLERANCES ARE		30~0.1 10~0.30 5~0.10 ~5	±0.30 ±0.20 ±0.15 ±0.10	ANGLE ±2°
			DRAWING NO.	SHEET 1 OF 1

GEPU 歌普