



SPECIFICATIONS

Current Rating:

3Amps

Insulator resistance:

5000 Megohms min.

Dielectric Withstanding:

AC 500V

Operating Temperature:

-40°T0 +105°C

Contact Material:

Brass

Plating:

Gold Flash

Insulator Material:

PA6T UL 94V-0

UNSPECIFIED TOLERANCE: ±0.20

Dimen Sions List

Contacts Per row	Dimensions		Contacts Per row	Dimensions	
	A	B		A	B
1	2.54	0	21	53.34	50.80
2	5.08	2.54	22	55.88	53.34
3	7.62	5.08	23	58.42	55.88
4	10.16	7.62	24	60.96	58.42
5	12.70	10.16	25	63.50	60.96
6	15.24	12.70	26	66.04	63.50
7	17.78	15.24	27	68.58	66.04
8	20.32	17.78	28	68.58	68.58
9	22.86	20.32	29	71.12	68.58
10	25.40	22.86	30	73.66	71.12
11	27.94	25.40	31	76.20	73.66
12	30.48	27.94	32	78.74	76.20
13	33.02	30.48	33	81.28	78.74
14	35.56	33.02	34	83.82	81.28
15	38.10	35.56	35	86.36	83.82
16	40.64	38.10	36	88.90	86.36
17	43.18	40.64	37	91.44	88.90
18	45.72	43.18	38	93.98	91.44
19	48.26	45.72	39	96.52	93.98
20	50.80	48.26	40	101.6	96.52

APPROVALS		DATE	GEPU歌普	
DRAWN	ZHIWEI.CHEN	2015.07.07		
CHECKED			TITLE: 2.54*2.54mm 90° SMT 常规	
APPROVALS			PART NO.	GP26-2520WVS-2xNP
TOLERANCES ARE		30~0.13 10~0.20 5~0.10	ANGLE	SCALE: 1:1
		±0.30 ±0.20 ±0.15	UNIT: mm	PROJ:
		±2°	DRAWING NO.	SHEET 1 OF 1
ECN NO.	REV.	DATE.	DESCRIPTION.	
	A		NEW	